

# Fluoropolymers for Coating Applications

by Barry Jones  
Halocarbon Products  
Corporation\*

**F**luorine polymers, commonly referred to as fluoropolymers, can greatly enhance the properties of coatings used in modern industrial, household, and construction products. The qualities of fluoropolymer resins and oligomeric additives make them an ideal solution for applications requiring a high resistance to solvents, acids, and bases, and—most importantly—an ability to significantly reduce friction.<sup>1</sup>

Such surfactant additives reduce surface energy while increasing chemical, UV, moisture, grease and dirt resistance, and surface lubricity. In addition to more common fluorinated olefin-based polymers, specialty fluorocrylates, fluorosilicone acrylates, fluorourethanes, and perfluoropolyethers/perfluoropolyoxetanes have been found to exhibit properties of interest for coatings applications.

Many of these new products are designed to address the concerns about perfluorooctanoic acid (PFOA) and perfluorooctanesulfonic acid (PFOS) associated with many existing fluoropolymer chemistries.

Coatings containing fluorochemicals find applications in electronics (photomask covers, anti-reflection coatings), construction (highly protective coatings for exterior substrates), cool-roof coatings, and optics (antifouling coatings for eyeglass lenses and liquid crystal displays). Other general coatings that may contain fluoropolymers include floor polishes, wood stains, automotive clearcoats, as well as ink jet inks, pigment dispersions, and adhesives.

In this article, we will review the properties of fluorochemicals and their numerous variations. We will also analyze current uses and technical applications, and how they might be utilized differently for future coatings applications.

## FLUORINE ATOM PROPERTIES

Unique characteristics of the fluorine atom result in the interesting properties of polymers that contain them.<sup>2</sup> A fairly small atom, fluorine has very low polarizability and high electronegativity. Because there is a

\*P.O. Box 661, River Edge, NJ 07661.

high degree of overlap between the outer orbitals of fluorine and the corresponding orbitals of second period elements, bonds formed between carbon and fluorine are very strong. The higher bond energy of the C-F bond compared to the C-H bond leads to greater thermal stability.

Perfluoropolymers, which contain only C-F bonds, have excellent chemical and weather resistance.<sup>3</sup> The small dipole moment of these compounds also contributes to their oil and water repellancy, as well as their low surface tension, low refractive index, low friction coefficient, and reduced adhesion to surfaces.<sup>1</sup>

Partially fluorinated polymers exhibit a strong electron attracting ability, resulting in a high dielectric constant and optical activity. In small molecules, this attribute leads to enhanced acidity and lipophilicity and the ability to block metabolic pathways, making fluorine-substituted compounds ideal as pharmaceuticals.<sup>2</sup>

Other characteristics of fluoropolymers determined by the strength of the C-F bond and the low polarizability and high electronegativity of fluorine include soil resistance, insulating properties, and the ability to act as a gas barrier.<sup>1</sup>

## PTFE AND FRIENDS—A BRIEF MENTION

The most common commercially available fluoropolymers are based on monomers of tetrafluoroethylene, vinylidene fluoride, and chlorotrifluoroethylene.<sup>3</sup> Both homopolymers and copolymers of these three monomers with compounds such as perfluoroalkyl vinyl ethers, hexafluoropropylene, chlorotrifluoroethylene, and perfluorobutyl ethylene exhibit increased chemical and flame resistance, photo and thermal stability, and enhanced lubricity when compared to their non-fluorine containing counterparts.

These fluoropolymers find use in many applications, including chemical process equipment liners, insulating coatings for electronics, non-stick coatings for cookware, surgical patches, and glass fiber fabric coatings used for roofing of large structures. Polytetrafluoroethylene (PTFE) and polyvinylidene fluoride (PVDF) are the fluoropolymers most widely used for these types of applications.

PTFE and other similar homopolymers can also be added directly to a coating formulation. In this case they function like waxes, reducing friction and increasing wear and scratch resistance.<sup>3</sup> With both hydrophobic and oleophobic characteristics, the fluorinated portions of the polymer tend to migrate to the surface of the coating, providing the desired properties.

While PTFE and similar products may be the most widely recognized fluoropolymers, there are significant limitations to their use in many applications. These

## Beneficial Properties of Fluoropolymers for Coating Formulations

- Low surface energy
- Chemical and moisture resistance
- Oil and grease resistance
- Adhesion to low energy surfaces
- Low refractive index
- Surface lubricity
- Soil/dirt resistance
- Heat resistance
- Abrasion resistance
- Vapor permeability
- UV resistance
- Non-stick characteristics
- Excellent electrical insulation and dielectric properties

polymers require high temperature processing and thus can only serve in coatings for temperature resistant materials. The very high crystallinity of the fluoropolymers means they are poorly soluble in typically used organic solvents, further limiting their processability.


Incorporation of some amount of non-fluorinated monomers (ethylene or substituted derivatives, for example) into polymers prepared from fluorinated compounds like tetrafluoroethylene, chlorotrifluoroethylene, or other fluorinated olefins results in copolymers with amorphous structures that retain much of the desired properties of pure fluoropolymers but exhibit improved solubilities and have lower process temperatures.<sup>3</sup>

Monomers containing reactive functional groups also have been found to improve processability while adding new physical attributes.<sup>6</sup> These more specialized fluoropolymers have been employed as binders and/or surfactants in numerous coating applications. Fluoroacrylates have been commercially available for the longest time. Compounds receiving attention in recent years include fluorosilicone acrylates, fluorourethanes, and perfluoropolyethers/perfluoropolyoxetanes.


## Possible Characteristics of Coatings Containing Fluoropolymers

- Improved weatherability
- Improved wettability
- Improved corrosion resistance
- Improved stain resistance
- Easy to clean
- Enhanced durability/stability in extreme environments
- Improved flow, leveling, adhesion, gloss, clarity, etc.
- Smoother finishes (reduction of surface blemishes)
- Enhanced release properties
- Enhanced anti-static properties
- Fire-retardancy

(1)  $C_4F_9SO_2N(CH_3)C_6H_4OC(O)CH=CH_2$




Scheme A—Fluorinated acrylate monomers (reference 7).




Scheme B—Alcohols and diols containing perfluorinated side chains (reference 11).


**Fomblin Y<sup>®</sup>**




**Poly hexafluoroacetate  
Demnum<sup>®</sup>**



Scheme C—PFPE compounds (reference 17).



Mixture of cis and trans 2,6-bis(trifluoromethyl)-1,1,1,7,7,7-hexafluoro-3-heptene-2,6-diol



Mixture of cis-2,6-bis(trifluoromethyl)-1,1,1,7,7,7-hexafluoro-4-methyl-3-heptene-2,6-diol and 1,1-bis(trifluoromethyl)-1,1,1,7,7,7-hexafluoro-2-propenyl ethylene

Scheme D—Examples of diols available from Halocarbon which can be used in coatings applications to prepare urethane polymers.

## FLUOROACRYLATES

Acrylic fluorinated copolymers have been used for a wide variety of applications, including anti-graffiti and easy clean coatings,<sup>7</sup> release coatings/liners in pressure sensitive adhesives,<sup>7</sup> treatments for paper, paperboard and leather,<sup>8</sup> as penetrating sealers for porous surfaces,<sup>9</sup> and as protective coatings for electronic applications.<sup>9</sup>

Poly(hexafluoropropylene oxide), poly(difluoromethylene oxide-co-tetrafluoroethylene oxide), and N-methyl perfluorobutanesulfonamidoethyl acrylate are examples of raw materials used for the production of fluoroacrylate polymers.<sup>7</sup> Fluorinated methacrylates have also been investigated for the synthesis of fluoropolymers with reduced polymerization shrinkage, improved strength, and high hydrophobicity characteristics.<sup>10</sup>

Perfluoroalcohols containing branching perfluoroalkyl groups have been synthesized with the aim of making polyfluoroacrylates that contain perfluoro groups that extend out from the polymer backbone.<sup>11</sup> The fluorine content can be controlled with the size of the perfluoroalkyl groups incorporated. It is proposed that the branching structure in the fluoropolymer would form a protective outer layer and keep the polymer backbone from being exposed to harsh environments.

## FLUROSILICONE ACRYLATES

Like fluoropolymers, silicone-based compounds provide many properties of value to coatings formulators. Hydrophobicity, wettability, leveling, mar and slip resistance, and transfer resistance can all be significantly enhanced depending on the chemistry of the silicon-based resin or additive used.<sup>6</sup> Fluorosilicone polymers have been prepared that exhibit the advantageous characteristics of both fluorine- and silicon containing materials.

In general, polysiloxanes containing fluorinated side groups are the easiest to prepare. Acrylate-fluorosilicone alternating and block copolymers are another type. These compounds have a lower resistance to corrosive chemicals than pure fluoropolymers, but do have low surface energy and remain flexible at temperatures as low as  $-60^{\circ}\text{C}$ .<sup>12</sup> They also can be further modified via different silicone crosslinking mechanisms.<sup>13</sup> These fluoroacrylates may have application in marine antifouling coatings.<sup>6</sup>

## FLUORURETHANES

Polyfluorourethanes can be produced from fluorinated diols and a traditional diisocyanate, or a fluoro-





2010 and complete elimination by 2015.<sup>20</sup> All eight companies accepted the challenge, and some have already developed alternative products and are introducing them to the marketplace.

Fluorotelomers (C-6 or lower products) are not produced using PFOA and these short chain molecules cannot breakdown to PFOA in the environment. When properly designed, they exhibit similar characteristics to larger-chain fluoropolymers. These more environmentally acceptable alternatives also appear to require little change in the coating production process, helping make the transition to this newer technology go more smoothly.

## CONCLUSION

Fluorine-rich polymers exhibit a wide range of properties that make them ideal as surfactants and binders in high performance coatings. The unique combination of chemical and thermal stability, low dielectric constant, and low surface energy has led to growing interest in fluoropolymers for a wide range of applications.

Development of novel copolymers of perfluorinated alcohols, ethers, urethanes, acrylates, siloxanes, and other compounds has expanded the potential scope of applications even further. Demand for cost effective, high performing, multifunctional coatings that enable materials to perform efficiently and effectively under extreme conditions with minimal environmental impact (energy consumption, VOC emissions, toxicity, carbon footprint, etc.) continues to increase. These specialty fluoropolymers possess many characteristics that make them ideally suited for use in such novel coating formulations.

Recognition of the environmental issues surrounding higher chain length fluoropolymers has led producers to increase research efforts for the identification of short chain alternatives that provide similar performance characteristics. These efforts will result in the development of additional new fluorochemicals and ensure the continued growth of the fluoropolymer market. □

## References

- (1) (a) Features and Applications of Fluorochemicals, <http://www.daikin.com/chm/fluoro/index.html>, Daikin Industries website, <http://www.daikin.com>; (b) Solvay Solexis-

- A Leader in Fluorinated Material, [http://www.solvaysolexis.com/products/0\\_10503-2-0.00.htm](http://www.solvaysolexis.com/products/0_10503-2-0.00.htm), Solvay Solexis website, [www.solvaysolexis.com](http://www.solvaysolexis.com), accessed 3/17/08.
- (2) Organofluorine Chemistry, [http://bama.ua.edu/~chem/seminars/student\\_seminars/spring05/papers-s05/LHural-sem.pdf](http://bama.ua.edu/~chem/seminars/student_seminars/spring05/papers-s05/LHural-sem.pdf), University of Alabama website, <http://www.ua.edu>, published 2005, accessed 3/17/08.
- (3) Basic Features of Fluoropolymers, <http://www.daikin.com/chm/pro/kasei/fluoro/index.html>, Daikin Industries website, <http://www.daikin.com>, accessed 3/17/08.
- (4) Wakefield, B., "Fluorinated Pharmaceuticals," *Innov. Pharm. Tech.*, 74 (2002).
- (5) Ionescu, S., "Introduction to Fluoropolymers," [http://fluoroconsultants.com/db4/00322/fluoroconsultants.com/\\_download/INTRODUCTIONTOFLUOROPOLYMERS.pdf](http://fluoroconsultants.com/db4/00322/fluoroconsultants.com/_download/INTRODUCTIONTOFLUOROPOLYMERS.pdf), FluoroConsultants Group website, <http://fluoroconsultants.com>, accessed 3/17/08.
- (6) Morrison, S., "Fluorochemicals: Performance at a Price," *SpecialChem4Coatings.com*, Dec. 7, 2005, <http://www.specialchem4coatings.com/resources/articles/article.aspx?id=4345>, accessed 3/17/08.
- (7) Liu, J.L., Moore, C., and Pellerite, G.L., "Compositions Containing Photosensitive Fluorochemical and Uses Thereof," [www.3m.com](http://www.3m.com), 3M Innovative Properties Company, June 7, 2006.
- (8) DuPont Zonyl® Fluorochemical Intermediates, [http://www.dupont.com/Zonyl\\_Fluorochemical\\_US/products/zonyl\\_pggs/intermediates.html](http://www.dupont.com/Zonyl_Fluorochemical_US/products/zonyl_pggs/intermediates.html), DuPont website, [www.dupont.com](http://www.dupont.com), accessed 3/18/08.
- (9) Eijlsma, S., "Flexible Circuitry Technology Background and Important Fundamental Issues," *Circuit World*, 25, No. 2, 6 (1999).
- (10) Chin, K.M. and Stansbury, J.W., "New Families of Photocurable Oligomeric Fluoromonomers for Use in Dental Composites," *Chem. Mater.*, 8, 12, 2704 (1996).
- (11) Kawa, H., Bierschenk, T.R., Juhlke, T.J., and Lagow, R.L., "Synthesis of Unique Fluorinated Diols," presented at Fluorine in Coatings III, Orlando, FL, January 25-27, 1999.
- (12) Owen, M.L., *Surf. Coat. Int.*, 71 (2004).
- (13) *Europ. Coat. J.*, 7 8, p. 34, 36-38 (2005).
- (14) Redlow, S.L. and Stump, E.C., Jr., "Preparation of Highly Fluorinated Polyurethanes," NASA Technical Reports, 1971.
- (15) Fluoroethane Hydrophobic and Superhydrophobic Coatings, <http://www.cytotix.com/coatings.html>, Cytonix Corporation website, [www.cytotix.com](http://www.cytotix.com), accessed 3/18/08.
- (16) Background, <http://www.fpu-coatings.com/AboutUs.html>, 21st Century Coatings, Inc.-USA website, [www.fpu-coatings.com](http://www.fpu-coatings.com), accessed 3/18/08.
- (17) Electronic Fluids, Solvay Solexis, <http://www.solvaysolexis.com/Electronic%20Fluids.htm>, accessed 3/17/08.
- (18) PolyFox: A novel Fluorochemical, FACT SHEET: PolyFoxT Fluorochemicals, <http://www.omnova.com/products/chemicals/PolyFox.aspx>, OMNOVA Solutions Inc. website, [www.omnova.com](http://www.omnova.com), accessed 3/17/08.
- (19) (a) Ellis, et al., "Degradation of Fluorotelomer Alcohols: A Likely Atmospheric Source of Perfluorinated Carboxylic Acids," *Environ. Sci. Technol.*, 38, 3316 (2004); (b) Dinglasan, et al., "Fluorotelomer Alcohol Biodegradation Yields Poly- and Perfluorinated Acids," *Environ. Sci. Technol.*, 38, 2857 (2004).
- (20) 2010/15 PFOA Stewardship Program, <http://epa.gov/opptintr/plua/pubs/ploastewardship.htm> on the U.S. Environmental Protection Agency Perfluorooctanoic acid (PFOA) and Fluorotelomers website, <http://epa.gov/opptintr/pfoa/index.htm>, accessed 5/1/08.